

# SAFTY DATA-SHEET

according to 91/155/EWG and §14 of the Hazardous Substances Order  
Date of Publication: 25. Februar 2003 Revised on 29/07/2004

---

## Description of the substance, its Formulation and company name

Trade name: Sehestedt's HARD RESIN OIL German: Fußbodenhartharzöl

---

Art.No.: 2150

---

### Manufacturer and supplier:

Sehestedter Naturfarben

Alter Fährberg 7

D-24814 Sehestedt

Tel.: 0049 4357 1049

### Ingredients in decreasing concentration:

Linseed oil

Linseed standoil

Tungoil standoil

Boiled down castor oil

Shell-Sol T (Isoaliphate)

Resinester

Orange peel oil

### Transport reference:

Classification: not registered - not dangerous

UN No. -

ADR/RID -

GGVSee/IMO-IMDG Code -

ICAO/IATA-DGR -

There are no specific requirements under national or international regulations for the transportation by sea, road, rail or air.

### Labelling:

Labelling according to EEC directives: This product has not to be labbed in accordance to EEC guideline on classification and labelling.

### Flammability:

Flammable with a flashpoint between 21 and 61°C

Ignitionpoint: 220°C

### Transport reference:

Classification: not registered - not dangerous

UN No. -

ADR/RID 3/31c

GGV/See/IMO -IMDG Code UN-No.: 1306

ICAO/IATA-DGR UN-No. 1306

There are no specific requirements under national or international regulations for the transportation by sea, road, rail or air.

### Storage:

Keep container tightly locked.

Store in a cool, dry place, protect from freezing

### Handling:

Avoid eye contact

### First aid measures:

Eye contact: wash with water or neutral eyewash solution.

Skin contact: wash with soap and water. Do not use solvents.