

Sehestedt's Wall Glazing Ground

A solvent-free, washable, radiant white, matte wall coating with good filling and coverage quality for interior use on all higher impact surfaces in kitchens, baths, etc. This highly gas and vapour permeable casein-wax-resin dispersion paint is particularly suitable as a fast glazing ground. On this watercolor ground plant colors and other suitable pigments are easily and durably applied with Sehestedt's Glaze Binder (Art. Nr. 2600).

Sehestedt's Casein Glazing Ground is easy to apply, it is anti-static, reduces dust build-up in living areas, allows easy redecoration - simply paint over, has good coverage quality on solid surfaces. Materials as quartz or cellulose flakes can be blended in for wall structuring.

Ingredients, in decreasing concentration: soft water, Dolomite rock meal, talcum, China-clay, finest glimmer, titan dioxide, sasein (New Zealand), beeswax-and shellac soap, natural latex milk, borax, castor oil, dammar resin, methyl cellulose and bentone soil.

Solvent-free!!!

Storage: store in a cool, dry place, protect from freezing. Unopened containers can be kept for up to 6 months.

Preparation: subsequent plant color glazing is best possible on walls papered with oatmeal wallpaper that has been coated with Casein Glazing Ground. Lime-cement plasteer must be neutralized with alum, gypsum plaster with Sehestedt's Wall Saler. Plant colors will neither tolerate an acidic nor an alkaline undercoat.

If glazing should not be intended or a brilliant white coat not be necessary, the amount of titan dioxide in the product will be considerably reduced. There we recommend the application of Casein Binder Paint (Art.Nr. 2550) which is old-white and can be perfectly tinted with soil pigments. It is sold at a good price.

Application and coverage: one 10.0 l container is sufficient for approx. 60 - 80 m² brilliant white wall surface. The surface should be checked very carefully for irregularities as every defect will be all too obvious after subsequent glazing, so better for a second coat.

Do not glaze before complete hardening (approx. 1 - 2 days).

Sehestedt's Natural Colors offers two different binder systems or wall glazing.

Sehestedt's Glazing Binder with Chitosan

Sehestedt's Chito Glazing Binder is an oil/water emulsion produced with the natural emulsifier chitosan from the selected pure natural raw materials: water, a special combination of plant oils and chitin/chitosan from the shells of crustacea, a raw material similar to cellulose producing a horn-like, breathable surface and having a preserving effect.

A water dilutable binder for soil, mineral color wall glazes on white, reflecting surface (best with casein Wall Glazing Ground Art. Nr. 2560).

It can also be used as medium in tempera painting. After drying it is wipe- and wash-fast, elastic, physiologically safe.